



42U Vertical Rack Mount 18 Way Schuko Socket 1,8 m. 3x2,5 mm² Power Cable
Power Distribution Unit with 2x16A Circuit Breaker

HIGHLIGHTS

- Vertical Rack Mountable
- Rotating Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

OPTIONS

- Fixed Plastic Mounting Ear Option
- Cable Length/Plug type on demand
- Socket Number on Demand
- Color Options

THE PACKAGE INCLUDES

- PDU
- Screw&Nut Set for installation

DESIGN & MATERIAL

Plastic Material	Fire Retardant Nylon 6 v0 or v2
Body Material	Aluminum Body
Sockets	2x9 Schuko Sockets (DIN 49440)
Cable Options	1,5 m. / 1,8 m. / 2 m. / 3 m. / 5 m. 3x1,5 mm ² / 3x2,5 mm² / 3x4 mm ² / 3x6 mm ²
Rack Mount	Vertical Rack Mountable
Contacts	Brass
Protection	2x16A Circuit Breaker ON/OFF Switch Surge Protect Voltmeter/Ampermeter Multimeter
Certificate	CE
Warranty	Lifetime (On production based defects)

ELECTRICAL & ENVIROMENTAL

Cable Plug Type Options	CEE NORM 32A (EN60309) UPS, (FRENCH/DIN49441) SCHUKO (GERMAN/DIN 49440) UK 13A (BS1363) IEC 320 (C14&C20)
Max. Output power	7000W (220V)
Nominal Input Voltage	100-240VAC
Max. Total Current Draw	32A
Operable Humidity	% 5-95
Operable Temperature	-5°C to +45°C
Storage Temperature	-25°C to +65°C



