



Vertical 1U Rack Mount 12 Way UK Socket 1,5 mt. 3x1,5 mm<sup>2</sup> Cabled UPS Plug  
Power Distribution Unit (PDU) with 16A Circuit Breaker and Plastic Rack Mount Ears

### HIGHLIGHTS

- Rack Mountable
- Plastic Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

### OPTIONS

- 4-Way Rotating Metal Ear Option
- Cable Length/Plug type on demand
- Socket Number Options
- Color Options

### THE PACKAGE INCLUDES

- PDU
- Screw&Nut Set for installation

### DESIGN & MATERIAL

Plastic Material	Fire Retardant Nylon 6 v0 or v2
Body Material	Aluminum Body
Sockets	12xUK Sockets (BS1363)
Cable Options	1,5 Mtr / 1,8 Mtr / 2 Mtr / 3 Mtr / 5 Mtr 3x1,5 mm <sup>2</sup> / 3x2,5 mm <sup>2</sup> / 3x4 mm <sup>2</sup> / 3x6 mm <sup>2</sup>
Rack Mount	Vertical 1U Rack Mountable Plastic Rack Installation Ears
Contacts	Contacts: Phosphor bronze Bus bar: Brass
Protection	16A Circuit Breaker On/Off Switch Surge Protect
Certificate	CE
Warranty	Lifetime (On production based defects)

### ELECTRICAL & ENVIROMENTAL

Cable Plug Type Options	CEE NORM 32A (EN60309) UK 13A (BS1363) UPS (FRENCH) SCHUKO (GERMAN/DIN 49440) IEC 320 (C14&C20)
Max. Output power	4000W (220V)
Nominal Input Voltage	100-240VAC
Max. Total Current Draw	16A
Operable Humidity	% 5-95
Operable Temperature	-5° C to +45° C
Storage Temperature	-25° C to +65° C



